

Wash Fastness 세탁견뢰도 시험기

WASH COLOR FASTNESS TESTER



DL-2002 Series



ISO 품질시스템 인증



제품의 특징

- PID 방식의 온도 컨트롤러와 임의로 시간 설정이 가능한 디지털 타이머가 장착되어 있다. (Touch Screen)
- 구동 모터에 과부하가 걸리지 않도록 인버터를 장착하여 작업 시작과 끝이 부드럽게 동작하도록 설계되어 있다.
- 홀더에 스프링이 장착되어 Pot를 밀어서 돌리면 쉽게 탈부착이 가능하다. 550mL, 1200mL Pot를 병행하여 사용 가능하다.
- 고온에서 Pot에 누수 현상을 방지하기 위하여 특수 패킹을 사용하였다.
- 사용자의 편의를 위하여 도어에 Shock Absorber가 장착되어 있다.
- 작업 종료를 알리기 위한 버저(Buzzer)가 내장되어 있다.
- 사용자가 쉽게 조작할 수 있고 청소가 간편하다.
- 시험 규격 : KSK 0430, ISO 105-C06, ISO 105-C08, AATCC 61

Specification

Model	DL-2002	DL-2002S	DL-2002M	DL-2002L
Number of pecimen	12pots (550mL x 12pots)	12pots (1200mL x 12pots)	12pots (550mL x 12pots) 12pots (1200mL x 12pots)	20pots (550mL x 20pots) 20pots (1200mL x 20pots) - Option
Test pot	550mL x 12ea (Standard)	1200mL x 12ea (Standard)	550mL x 12ea (Standard) 1200mL x 12ea (Standard)	550mL x 20ea (Standard) 1200mL x 20ea (Option)
Temp. controller	7" Color touch panel			7" Color touch panel
Temp. range	25~99°C			25~99°C
Temp. accuracy	±0.5°C at 50°C			±0.5°C at 50°C
Rotating speed range	40±2r/min.			40±2r/min.
Material	Internal - SUS#304 polishing External - SUS#304 H/L			Internal - SUS#304 polishing External - SUS#304 H/L
Test timer	99min. 59sec.			99min. 59sec.
Heater capacity	7800W			9000W
Driver motor	200W (Inverter control)			750W (Inverter control)
Power source	220VAC 50/60Hz single phase, 8.5kW			220VAC 50/60Hz single phase, 9.5kW
Weight (Approx.)	180kg (±5kg)			220kg (±5kg)
Dimension (Approx.)	1130(W) x 840(D) x 1100(H)mm			1400(W) x 840(D) x 1100(H)mm

Feature

- PID type temperature controller and re-settable digital timer. (Touch Screen)
- Soft start and brake by inverter not to overload driving motor.
- Easy to replace pots on coil spring holer incorporating a push and twist feature.
- Model DL-2002M : Interchangeable pots. (550mL small size and 1200mL large size)
- Leak proof pots at high temperature with a suitable rubber gasket.
- Equipped with door shock absorber for operator convenience.
- Auto-alarm after working finish.
- Convenient operation and cleaning.
- Standards : KSK 0430, ISO 105-C06, ISO 105-C08, AATCC 61



Control panel



Pot holder (Only 550mL)



Pot holder (550mL & 1200mL)

Accessories



Test pot (550mL)



Test pot (1200mL)