

Bursting Strength

PNEUMATIC BURSTING STRENGTH TESTER
파열강도 시험기 (공압식)



DL-3004P



ISO 품질시스템 인증

제품의 용도 및 특징

- 다양한 직물, 부직포, 가죽 및 기타 재료에 사용되며, 경사/위사 및 모든 방향으로 동시에 힘을 가할 때 (Elastic Diaphragm Method) 팽창력과 팽창도의 성능이 결정된다.
- 국제 표준 규격에 부합한 클램프 장치로 조작이 편리하다.
- 테스트 샘플 미끄럼 방지를 위한 에어 클램프 시스템을 적용하여 테스트 시간을 단축할 수 있다.
- 사용이 편리한 터치식 화면을 적용하여 데이터 확인 및 인터페이스 통신 지원이 가능하고, 영문 메뉴로 구성되어 있다.
- 측정 단위를 사용자가 쉽게 선택 변환하여 사용이 가능하다. (KPa, PSI, bar)
- 시험 규격 : ASTM D 3786, ISO 13938-2


Purpose and Feature

- Use for various woven fabrics, nonwoven, leather and other materials, determined the performance of the expansive force and expansion diagram when applying forces at the same time in all directions of wrap / weft (Elastic Diaphragm Method).
- Easy to operate because of suitable clamp system of international standard.
- Reduce the test time by applying the air clamp system to prevent slipping the sample test.
- User friendly touched LCD possible to check the data and support the interface communication, consist of English menu.
- Easy to change and use the measuring units by user. (KPa, PSI, bar)
- Standard : ASTM D 3786, ISO 13938-2

Accessories



Dome



Nozzle



Strip printer



Dome and clamp



Clamp ring



Rubber membrane



Distance calibrator



Pressure calibrator

Specification

Model	DL-3004P
Measuring range	1MPa (0.2~900KPa)
Clamp	Air clamp
Controller	LCD touch panel
Test bells	7.3 cm ² (Dia. 30.5mm), 50cm ² (Dia. 79.8mm) - Standard 10 cm ² (Dia. 35.7mm), 100 cm ² (Dia. 112.8mm) - Option
Rubber membrane	Outer dia. 80mm, Thickness 1.5±0.1mm
Max. distension	70mm
Pressurization time	100~500ml/min.
Output	Record printer output
Power source	220VAC 50/60Hz single phase, 200W
Weight (Approx.)	205kg (±5kg)
Dimension (Approx.)	700(W) x 760(D) x 1465(H)mm

대림스타릿(주)

34, Okguchenondong-ro, Siheung-si, Gyeonggi-do, Korea
Tel. +82-31-499-6446 Fax. +82-31-499-6448

The specifications are subject to alter or modify the appearance without notice.

www.daelimlab.com

e-mail : dl1001@daelimlab.com

2023. 02